

A note on movement in logical grammar*

Glyn Morrill

Department of Computer Science, Universitat Politècnica de Catalunya

ABSTRACT

In this article we make some brief remarks on overt and covert movement in logical grammar. With respect to covert movement (e.g. quantification) we observe how a treatment in terms of displacement calculus interacts with normal modalities for intensionality to allow a coding in logical grammar of the distinction between weak and strong quantifiers (i.e. those that may or may not scope nonlocally such as a and every respectively). With respect to overt movement (e.g. relativisation) we observe how displacement calculus can support a coding of a linear filler-gap dependency similar to that employed in lambda grammars, but we argue that this general approach does not extend to either the multiplicity nor the island-sensitivity of parasitic gaps, for which we advocate instead treatment in terms of a bracket-conditioned contraction subexponential.

Keywords:
covert and overt
movement;
parasitic
extraction;
relativisation;
weak and strong
quantification

1 COVERT MOVEMENT: QUANTIFICATION

Montague's rule S14 of quantification (ignoring pronoun binding) can be expressed:

$$\frac{\Delta(N: x) \Rightarrow S: \omega}{\Delta(QP: \chi) \Rightarrow S: (\chi \lambda x \omega)}$$

*Research partially supported by an ICREA Acadèmia 2012, and by SGR2014-890 (MACDA) of the Generalitat de Catalunya, and grants APCOM TIN2014-57226-P and TIN2017-89244-R from MINECO (Ministerio de Economía, Industria y Competitividad). I am grateful to three reviewers for their valuable comments and suggestions.

I.e. quantifier phrases occupy nominal positions and take semantic scope at the sentence level, applying to the lambda abstraction of the sentence context over the meaning of the nominal position occupied. Montague's rule allows any quantifier to take scope at the level of any superordinate clause, correctly generating for example de re and de dicto readings of:

- (1) John thinks a spy sleeps.

But incorrectly overgenerating two readings of e.g.

- (2) John thinks every spy sleeps.

The logical rules of the calculus of Lambek (1958) are as follows, where $\Delta(\Gamma)$ signifies context configuration Δ with a distinguished sub-configuration Γ . We add the product unit I (such that $I \bullet A \Leftrightarrow A$ and $A \Leftrightarrow A \bullet I$) and include the metalinguistic empty antecedent Λ .

$$\begin{array}{ccc}
 \frac{\Gamma \Rightarrow B \quad \Delta(C) \Rightarrow D}{\Delta(C/B, \Gamma) \Rightarrow D} /L & & \frac{\Gamma, B \Rightarrow C}{\Gamma \Rightarrow C/B} /R \\
 \\
 \frac{\Gamma \Rightarrow A \quad \Delta(C) \Rightarrow D}{\Delta(\Gamma, A \setminus C) \Rightarrow D} \setminus L & & \frac{A, \Gamma \Rightarrow C}{\Gamma \Rightarrow A \setminus C} \setminus R \\
 \\
 \frac{\Delta(A, B) \Rightarrow D}{\Delta(A \bullet B) \Rightarrow D} \bullet L & & \frac{\Delta \Rightarrow A \quad \Gamma \Rightarrow B}{\Delta, \Gamma \Rightarrow A \bullet B} \bullet R \\
 \\
 \frac{\Delta(\Lambda) \Rightarrow A}{\Delta(I) \Rightarrow A} IL & & \frac{}{\Lambda \Rightarrow I} IR
 \end{array}$$

Using Lambek's system requires lexical ambiguity to obtain both sentence left-peripheral quantification (e.g. Everyone loves Mary) and right-peripheral quantification (e.g. John loves someone):

- (3) a: $(S/(N \setminus S))/CN: \lambda x \lambda y \exists z [(x z) \wedge (y z)]$
 a: $((S/N) \setminus S)/CN: \lambda x \lambda y \exists z [(x z) \wedge (y z)]$
 every: $(S/(N \setminus S))/CN: \lambda x \lambda y \forall z [(x z) \rightarrow (y z)]$
 every: $((S/N) \setminus S)/CN: \lambda x \lambda y \forall z [(x z) \rightarrow (y z)]$

And would require still further lexical ambiguity for medial quantification:

(4) John sent every student to Mary.

Moot and Retoré (2016) give a counting argument showing that in the Lambek calculus no finite number of lexical entries can generate all $n!$ quantifier scoping proofs.

In the Lambek calculus $(\backslash, \bullet, /; \Rightarrow)$ is a residuated triple:

(5) $B \Rightarrow A \backslash C$ iff $A \bullet B \Rightarrow C$ iff $A \Rightarrow C/B$

The Lambek calculus is a logic of concatenation, with the inference of the residuated triple $\{\backslash, \bullet, /\}$ hinging on the metasyntactic concatenative comma “,”. To account also for discontinuity Morrill, Valentin and Fadda (2011) define the displacement calculus. In the displacement calculus types are sorted by naturals according to the number of points of discontinuity their expressions contain. In addition to a residuated triple $\{\backslash, \bullet, /\}$ of continuous connectives there are residuated discontinuous connectives $\{\downarrow_k, \odot_k, \uparrow_k\}$ for which inference hinges on the metasyntactic intercalation “ $|_k$ ” where the positive integer k indicates the point of discontinuity in question counting from the left (it defaults to 1 under omission.)

Configurations \mathcal{O} are defined by the following, where the separator 1 marks points of discontinuity:

(6) $\mathcal{O} ::= \Lambda \mid \mathcal{T}, \mathcal{O}$
 $\mathcal{T} ::= 1 \mid \mathcal{F}_0 \mid \mathcal{F}_{i>0} \{ \underbrace{\mathcal{O} : \dots : \mathcal{O}}_{i \text{ } \mathcal{O}'\text{s}} \}$

For a type A , its sort $s(A)$ is the i such that $A \in \mathcal{F}_i$. For a configuration Γ , its sort $s(\Gamma)$ is $|\Gamma|_1$, i.e. the number of points of discontinuity 1 which it contains.

Sequents are of the form:

(7) $\mathcal{O} \Rightarrow \mathcal{F}$ such that $s(\mathcal{O}) = s(\mathcal{F})$

The figure \vec{A} of a type A is defined by:

(8) $\vec{A} = \begin{cases} A & \text{if } s(A) = 0 \\ A \{ \underbrace{1 : \dots : 1}_{s(A) \text{ } 1'\text{s}} \} & \text{if } s(A) > 0 \end{cases}$

Where Γ is a configuration of sort i and $\Delta_1, \dots, \Delta_i$ are configurations, the fold $\Gamma \otimes \langle \Delta_1 : \dots : \Delta_i \rangle$ is the result of replacing the successive

1's in Γ by $\Delta_1, \dots, \Delta_i$ respectively. Where Γ is of sort i , the hyperoccurrence notation $\Delta\langle\Gamma\rangle$ abbreviates $\Delta_0(\Gamma \otimes \langle\Delta_1 : \dots : \Delta_i\rangle)$, i.e. a context configuration Δ (which is externally Δ_0 and internally $\Delta_1, \dots, \Delta_i$) with a potentially discontinuous distinguished subconfiguration Γ (continuous if $i = 0$, discontinuous if $i > 0$). Where Δ is a configuration of sort $i > 0$ and Γ is a configuration, the k th metalinguistic intercalation $\Delta|_k\Gamma$, $1 \leq k \leq i$, is given by:

$$(9) \quad \Delta|_k\Gamma =_{df} \Delta \otimes \underbrace{\langle 1 : \dots : 1 \rangle}_{k-1 \text{ 1's}} : \Gamma : \underbrace{\langle 1 : \dots : 1 \rangle}_{i-k \text{ 1's}}$$

i.e. $\Delta|_k\Gamma$ is the configuration resulting from replacing by Γ the k th separator in Δ .

The logical rules of the displacement calculus are as follows, where as we have said $\Delta\langle\Gamma\rangle$ signifies a configuration Δ with a potentially discontinuous distinguished subconfiguration Γ .

$$\begin{array}{c} \frac{\Gamma \Rightarrow B \quad \Delta\langle\vec{C}\rangle \Rightarrow D}{\Delta\langle\vec{C}/\vec{B}, \Gamma\rangle \Rightarrow D} /L \qquad \frac{\Gamma, \vec{B} \Rightarrow C}{\Gamma \Rightarrow C/B} /R \\ \\ \frac{\Gamma \Rightarrow A \quad \Delta\langle\vec{C}\rangle \Rightarrow D}{\Delta\langle\Gamma, A\setminus\vec{C}\rangle \Rightarrow D} \setminus L \qquad \frac{\vec{A}, \Gamma \Rightarrow C}{\Gamma \Rightarrow A\setminus C} \setminus R \\ \\ \frac{\Delta\langle\vec{A}, \vec{B}\rangle \Rightarrow D}{\Delta\langle A\bullet\vec{B}\rangle \Rightarrow D} \bullet L \qquad \frac{\Delta \Rightarrow A \quad \Gamma \Rightarrow B}{\Delta, \Gamma \Rightarrow A\bullet B} \bullet R \\ \\ \frac{\Delta\langle\Lambda\rangle \Rightarrow A}{\Delta\langle\vec{I}\rangle \Rightarrow A} IL \qquad \frac{}{\Lambda \Rightarrow I} IR \end{array}$$

$$\begin{array}{c}
 \frac{\Xi\langle\vec{A}:x\rangle\Rightarrow B:\psi}{\Xi\langle\vec{\Box A}:z\rangle\Rightarrow B:\psi\{\vee z/x\}}\Box L \qquad \frac{\Box\Xi\Rightarrow A:\phi}{\Box\Xi\Rightarrow\Box A:\wedge\phi}\Box R \\
 \\
 \frac{\Xi\langle\vec{A}:x\rangle\Rightarrow B:\psi}{\Xi\langle\vec{\blacksquare A}:x\rangle\Rightarrow B:\psi}\blacksquare L \qquad \frac{\Box\Xi\Rightarrow A:\phi}{\Box\Xi\Rightarrow\blacksquare A:\phi}\blacksquare R
 \end{array}$$

Figure 1:
Normal modalities, where \Box marks a structure all the types of which have main connective a box

$$\begin{array}{c}
 \frac{\Gamma\Rightarrow B \quad \Delta\langle\vec{C}\rangle\Rightarrow D}{\Delta\langle\vec{C}\uparrow_k\vec{B}\mid_k\Gamma\rangle\Rightarrow D}\uparrow_k L \qquad \frac{\Gamma\mid_k\vec{B}\Rightarrow C}{\Gamma\Rightarrow C\uparrow_k B}\uparrow_k R \\
 \\
 \frac{\Gamma\Rightarrow A \quad \Delta\langle\vec{C}\rangle\Rightarrow D}{\Delta\langle\vec{\Gamma}\mid_k A\downarrow_k C\rangle\Rightarrow D}\downarrow_k L \qquad \frac{\vec{A}\mid_k\Gamma\Rightarrow C}{\Gamma\Rightarrow A\downarrow_k C}\downarrow_k R \\
 \\
 \frac{\Delta\langle\vec{A}\mid_k\vec{B}\rangle\Rightarrow D}{\Delta\langle\vec{A}\circ_k B\rangle\Rightarrow D}\circ_k L \qquad \frac{\Delta\Rightarrow A \quad \Gamma\Rightarrow B}{\Delta\mid_k\Gamma\Rightarrow A\circ_k B}\circ_k R \\
 \\
 \frac{\Delta\langle 1\rangle\Rightarrow A}{\Delta\langle\vec{J}\rangle\Rightarrow A}JL \qquad \frac{}{1\Rightarrow J}JR
 \end{array}$$

Then for all of left-peripheral and right-peripheral and medial quantification à la Montague we require just single type assignments:

- (10) a: $((S\uparrow N)\downarrow S)/CN: \lambda x\lambda y\exists z[(x z) \wedge (y z)]$
 every: $((S\uparrow N)\downarrow S)/CN: \lambda x\lambda y\forall z[(x z) \rightarrow (y z)]$

Hence the rule of S14 is lexicalised in a single lexical type.

Morrill 1990 and Hepple 1990 invoke semantically active (\Box) and inactive (\blacksquare) normal modalities respectively for grammatical domains. These are normal (i.e. distributive) S4 modalities; the former for semantic, e.g. intensional or temporal, domains, and the latter for syntactic domains. Morrill 2015 combines these as shown in Figure 1. Adding these to displacement calculus we can approach the capture of clause-locality invoking sensitivity to intensionality:

- (11) a: $\blacksquare(((S\uparrow\blacksquare N)\downarrow S)/CN): \lambda x \lambda y \exists z [(x z) \wedge (y z)]$
 every: $\blacksquare(((S\uparrow N)\downarrow S)/CN): \lambda x \lambda y \forall z [(x z) \rightarrow (y z)]$
 John: $\blacksquare N: j$
 sleep: $\square(N \setminus S): \text{sleep}$
 spy: $\square CN: \text{spy}$
 thinks: $\square((N \setminus S)/\square S): \text{think}$

A subordinate clause such as the complement of thinks is an intensional domain $\square S$ and thus requires its elements to be modal at the moment of \square proof. There is no problem when either a or every scopes locally within an intensional domain since their lexical types, like all lexical types, are modal. But while the hypothetical subtype $\blacksquare N$ of a bears a modality, that N of every does not, and so only the former can take wide scope out of its intensional domain.

2 OVERT MOVEMENT: RELATIVISATION

In ACG (de Groote 2001) or Lambda Grammar (Muskins 2001) a relative pronoun is assigned type:

$$\lambda \rho \lambda \sigma. \sigma + \text{that} + (\rho \ 0): (N \multimap S) \multimap CN \multimap CN: \lambda x \lambda y \lambda z [(y z) \wedge (x z)]$$

But ACG has the KLM problem (Kubota, Levine, Moot; Muskins 2001, Kubota 2010, Kubota and Levine 2012, Moot 2014, Kubota and Levine 2015, section 4.1.2) whereby the nondirectional dependents of an argument to a higher order functor can commute. This is because $A \multimap B \multimap C \vdash B \multimap A \multimap C$. For example, in TV coordination the natural seeming translation of Lambek coordination would be to assign the coordinator type:

$$\lambda \rho_2 \lambda \rho_1 \lambda \beta \lambda \alpha. \alpha + (\rho_1 \ 0 \ 0) + \text{and} + (\rho_2 \ 0 \ 0) + \beta: X \multimap X \multimap X, \text{ where } X = N \multimap N \multimap S$$

Then

- (12) John saw and praised Mary.

gets assigned the following readings which are all incorrect except the first:

- (13) “J saw M and J praised M”
 “J saw M and M praised J”
 “M saw J and J praised M”
 “M saw J and M praised J”

The more general point is that all alternative terms overgenerate as well, which is argued in Moot (2014).

In HTLG (Kubota and Levine 2012) there are both directional Lambek connectives for continuity and a nondirectional linear connective for discontinuity. The KLM problem above is evaded by assigning a TV coordinator the directed type:

$$\text{and: } (X \setminus X) / X, \text{ where } X = (N \setminus S) / N$$

But directional (concatenative) and nondirectional (functional) types cannot freely interweave in HTLG: interpreting concatenation as function composition, only makes sense for functions from string position to string position (i.e. simple strings) and not for more complex functions; other things being equal, directed types cannot contain nondirectional subtypes. Thus, other things being equal, the assignment of a relative pronoun on the pattern of that for above for lambda grammar must be:

$$\text{that: } (CN \setminus CN) \upharpoonright (S \downarrow N): \lambda x \lambda y \lambda z [(y z) \wedge (x z)]$$

with an outermost nondirectional slash because the argument has a nondirectional slash to allow medial extraction. But this means there is a potential KLM problem for the $\upharpoonright (S \downarrow N)$ argument. For example, to generate the following we require or: $(X \upharpoonright X) \upharpoonright X, X = CN \upharpoonright (S \downarrow N)$:

(14) animal that or person who John saw today

However the same types overgenerate the following, where the right node raised $S \downarrow N$ is medial in one or both of the disjuncts.

- (15) a. *animal that outside or person who John saw today
 b. *animal that or person who inside John saw today
 c. *animal that outside or person who inside John saw today

In response to this Yusuke Kubota (personal communication) suggests that a relative pronoun be assigned type

$$\text{that: } (CN \setminus CN) / \wedge (S \downarrow N): \lambda x \lambda y \lambda z [(y z) \wedge (x z)]$$

where \wedge is the defined connective “bridge” of displacement calculus. That is, in this case the KLM problem would be resolved by use of an additional connective. But note that this use of an additional connective it is motivated by a desire to correct empirical predictions but is a technically anomalous addition to HTLG.

In determiner gapping in HTLG (Kubota and Levine 2013, 2016) there is a further remnant KLM problem (Kubota, personal communication):

- (16) a. Most cats like Alpo and (most) dogs (like) Whiskas.
 b. I like most cats and you (like) (most) dogs.

$$\lambda\rho_2\lambda\rho_1\lambda\phi\lambda\sigma.((\rho_1\ \phi)\ \sigma)+\text{and}+((\rho_2\ \lambda\chi\lambda\psi(\psi\ \chi))\ 0):(X\uparrow X)\uparrow X$$

where $X = (S\uparrow TV)\uparrow Q$

This overgenerates the following where the determiner and the transitive verb orders are not consistent in the conjuncts:

- (17) *Most cats like Alpo and John (likes) (most) dogs.
 (18) *John likes most dogs and (most) cats (like) Alpo.

This overgeneration arises because the left-to-right positions of the two discontinuous dependencies are not identified. For an account of gapping including determiner gapping without this problem, in terms of a version of displacement calculus, see Morrill and Valentín (2017); that formulation evades the overgeneration because in displacement calculus the discontinuous dependents are indexed for left-to-right position, allowing the parallel grammatical determiner gapping of (16) but not the nonparallel ungrammatical cases (17) and (18).

In displacement calculus a relative pronoun can be assigned type:

$$\text{that}:(CN\backslash CN)/((S\uparrow N)\odot I):\lambda x\lambda y\lambda z[(y\ z)\ \wedge\ (\pi_1x\ z)]$$

or

$$\text{that}:(CN\backslash CN)/\wedge(S\uparrow N):\lambda x\lambda y\lambda z[(y\ z)\ \wedge\ (x\ z)]$$

There is no KLM problem of any kind. However, we offer two reasons to question any use of a discontinuous linear operator for relativisation.

First, let us observe that using displacement operators for both quantification and relativisation risks running into an inconsistency. This is as follows: on the one hand, quantifiers must be allowed to scope out of, for example, subjects, which are (weak) islands, so to treat quantification displacement must be able to penetrate islands. But then, on the other hand, the linear proposal for relativisation above will fail to be sensitive to islands.

Second, nor do the linear proposals above take into account parasitic extraction:

Figure 2:
exponentials

$$\begin{array}{c}
 \frac{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, \Gamma_2) \Rightarrow B: \psi}{\Xi(\zeta; \Gamma_1, !A: x, \Gamma_2) \Rightarrow B: \psi} !L \quad \frac{\zeta; \Lambda \Rightarrow A: \phi}{\zeta; \Lambda \Rightarrow !A: \phi} !R \\
 \\
 \frac{\Xi(\zeta; \Gamma_1, A: x, \Gamma_2) \Rightarrow B: \psi}{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, \Gamma_2) \Rightarrow B: \psi} !P \\
 \\
 \frac{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, [\{A: y\}; \Gamma_2], \Gamma_3) \Rightarrow B: \psi}{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, [[\Gamma_2]], \Gamma_3) \Rightarrow B: \psi\{x/y\}} !C_{bb}
 \end{array}$$

(19) man that the friends of admire

Therefore I suggest to treat the mediality of extraction and the potential for parasitic extraction not via an island-insensitive discontinuous linear implication, but via a permutation and island-conditioned contraction (but not weakening) subexponential; see Figure 2 which uses a stoup (Girard 2011) to store the structurally modalised resources; this formulation is essentially like Morrill (2011) in that parasitic domains must be doubly bracketed in the linguistic input.¹ A relative pronoun is to bear the permutation and bracket-conditioned contraction subexponential on its hypothetical subtype:

$$\text{that: } (CN \setminus CN) / (!N \setminus S): \lambda x \lambda y \lambda z [(y z) \wedge (x z)]$$

When this subtype has been lowered into the antecedent, it can be moved into the local stoup by !L; then it can be copied into the stoups of any number of (doubly bracketed) parasitic domains by !C_{bb}; then it

¹ And the formulation stands in contrast to Morrill (2017) which has the contraction rule without brackets in the linguistic input:

$$\frac{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, [\{A: y\}; \Gamma_2], \Gamma_3) \Rightarrow B: \psi}{\Xi(\zeta \uplus \{A: x\}; \Gamma_1, \Gamma_2, \Gamma_3) \Rightarrow B: \psi\{x/y\}} !C_b$$

which gives rise to undecidability (Kanovich, Kuznetsov and Scedrov 2017), and which furthermore overgenerates parasitic extraction in which a whole island domain is a parasitic gap, such as as the subject island in the example:

*man that likes

which is due to Stepan Kuznetsov (personal communication).

can be moved into any local host position by $!P$. The stoup contents of the parasitic domains can themselves be copied into the stoups of any number of doubly bracketed parasitic subdomains $!C_{bb}$ and so forth, and then into local subhost positions by $!P$.

The bracket conditioning of contraction ensures that parasitic gaps can only appear within singly bracketed islands, hosted by a non-island gap; a discontinuous linear operator can deliver neither such multiple binding nor such island-conditioning.

The resulting picture, then, is one in which displacement calculus is used to characterise the covert movement of quantification, including employment of semantic modalities for the distinction between strong and weak quantifiers, but in which an exponential modality rather than a discontinuous linear operator is used for the overt movement of relativisation, for the reasons given above.

REFERENCES

- Philippe de Groote (2001), Towards Abstract Categorical Grammars, in Proceedings of the 39th Annual Meeting of the Association for Computational Linguistics (ACL), Toulouse.
- Jean-Yves Girard (2011), The Blind Spot, European Mathematical Society, Zürich.
- Mark Hepple (1990), The Grammar and Processing of Order and Dependency, Ph.D. thesis, University of Edinburgh.
- Max Kanovich, Stepan Kuznetsov, and Andre Scedrov (2017), Undecidability of the Lambek calculus with subexponential and bracket modalities, in Proc. FCT, volume 10472 of LNCS, pp. 326–340.
- Yusuke Kubota (2010), (In)flexibility of Constituency in Japanese in Multi-Modal Categorical Grammar with Structured Phonology, Ph.D. thesis, Ohio State University.
- Yusuke Kubota and Bob Levine (2015), Against ellipsis: Arguments for the direct licensing of non-canonical coordinations, *Linguistics and Philosophy*, 38(6):521–576, doi:10.1007/s10988-015-9179-7.
- Yusuke Kubota and Robert Levine (2012), Gapping as Like-Category Coordination, in Denis Bechet and Alexander Dikovsky, editors, *Logical Aspects of Computational Linguistics*, volume 7351 of Lecture Notes in Computer Science, pp. 135–150, Springer Berlin Heidelberg, ISBN 978-3-642-31261-8, doi:10.1007/978-3-642-31262-5_9, http://dx.doi.org/10.1007/978-3-642-31262-5_9.

Yusuke Kubota and Robert Levine (2013), Determiner Gapping as Higher-Order Discontinuous Constituency, in Glyn Morrill and Mark-Jan Nederhof, editors, *Formal Grammar: 17th and 18th International Conferences, FG 2012, Opole, Poland, August 2012, Revised Selected Papers, FG 2013, Düsseldorf, Germany, August 2013. Proceedings*, pp. 225–241, Springer, Berlin, Heidelberg, doi:10.1007/978-3-642-39998-5{_}14.

Yusuke Kubota and Robert Levine (2016), Gapping as hypothetical reasoning, *Natural Language and Linguistic Theory*, 34(1):107–156.

Joachim Lambek (1958), The mathematics of sentence structure, *American Mathematical Monthly*, 65:154–170, doi:10.2307/2310058.

Richard Moot (2014), Hybrid Type-Logical Grammars, First-Order Linear Logic and the Descriptive Inadequacy of Lambda Grammars, Technical report, LaBRI (CNRS), Bordeaux University.

Richard Moot and Christian Retoré (2016), Natural Language Semantics and Computability, <https://arxiv.org/pdf/1605.04122.pdf>.

Glyn Morrill (1990), Intensionality and Boundedness, *Linguistics and Philosophy*, 13(6):699–726.

Glyn Morrill (2015), Structural Ambiguity in Montague Grammar and Categorical Grammar, *The Linguistic Review*, 32(1):87–113, doi:10.1515/tlr-2014-0017.

Glyn Morrill (2017), Grammar Logicised: Relativisation, *Linguistics and Philosophy*, 40(2):119–163, doi:10.1007/s10988-016-9197-0, open access.

Glyn Morrill and Oriol Valentín (2017), A Reply to Kubota and Levine on Gapping, *Natural Language and Linguistic Theory*, 35(1):257–270, doi:10.1007/s11049-016-9336-x.

Glyn Morrill, Oriol Valentín, and Mario Fadda (2011), The Displacement Calculus, *Journal of Logic, Language and Information*, 20(1):1–48, doi:10.1007/s10849-010-9129-2.

Glyn V. Morrill (2011), *Categorical Grammar: Logical Syntax, Semantics, and Processing*, Oxford University Press, New York and Oxford.

Reinhard Muskens (2001a), Categorical Grammar and Lexical-Functional Grammar, in *Proceedings of the LFG01 Conference*, pp. 259–279, University of Hong Kong.

Reinhard Muskens (2001b), Lambda Grammars and the Syntax-Semantics Interface, in R. van Rooy and M. Stokhof, editors, *Proceedings of the Thirteenth Amsterdam Colloquium*, pp. 150–155, Amsterdam.

Glyn Morrill

This work is licensed under the Creative Commons Attribution 3.0 Unported License.

<http://creativecommons.org/licenses/by/3.0/>

